



# Tip Top Sizes

Guide to Winthrop Tip Top Dimensions

Size	Tube ID Fraction	Tube ID Decimal	Tube ID millimeter	XATS	XATM	XAT	XATW	ATM	AT	TTM	TT	AUSSIE	AUSSIE WIDE	KITE TOP
#10	10/64	.156	4.0	•	•			•		•				
#12	12/64	.187	4.8	•	•			•	•	•	•			
#14	14/64	.218	5.6	•	•			•	•	•	•			
#16	16/64	.250	6.4	•	•	•		•	•	•	•			
#18	18/64	.281	7.1	•	•	•		•	•	•	•			
#20	20/64	.313	7.9	•	•	•	•		•		•	•	•	
#22	22/64	.344	8.7			•	•		•		•	•	•	
#24	24/64	.375	9.5			•	•		•		•	•	•	
#26	26/64	.406	10.3			•	•		•		•	•	•	
#28	28/64	.438	11.1			•	•		•		•	•	•	•
#30	30/64	.469	11.9			•	•					•	•	
#32	32/64	.500	12.7			•	•					•	•	
#34	34/64	.531	13.5			•	•					•	•	
#36	36/64	.563	14.3			•	•					•	•	
Knot/Swivel Clearance				5/16"	5/16"	5/16"	7/16"	1/4"	5/16"	1/4"	5/16"	5/16"	7/16"	3/8"
Weight Class (pounds)				20&up	30&up	80&up	100&up	20&up	30&up	20&up	30&up	80&up	80&up	NA
Ball Bearing Assembly							•	•	•	•	•	•	•	
Deep Drop Assembly								•	•	•	•			
Bushing Assembly				•	•	•	•						•	
Roller Diameter				1/2"	11/16"	7/8"	57/64"	1/2"	5/8"	1/2"	5/8"	57/64"	57/64"	NA